



**TECHNICAL  
DATASHEET**  
**VARIOTRAC 180H**

CONTACT US :

1 Grande rue  
54540 MONTIGNY  
Tel : +33 (0)3 83 42 15 79



[WWW.PLAISANCE-EQUIPEMENTS.COM](http://WWW.PLAISANCE-EQUIPEMENTS.COM)







## ***VARIOTRAC 180H***

### **GENERAL INFORMATION**

Constructor	PLAISANCE EQUIPEMENTS SAS
Brand	Plaisance
Type	Self-propelled machine (MAGA)
Version	VARIOTRAC 180H
Power grip	Hydraulic

### **FEATURES**

Advancement	Hydrostatic advancement with 2 speed ranges 0-8 km/h and 0-25 km/h
	Suptronic advancement control (automatic adaptation of the self-propelled vehicle's advance according to the engine speed)
	Number of axles and wheels : 2 motorized steering axles DANA type 212/420 and 212/421, 4 simple wheels
	4 driving wheels
	Steering mode : – 2 front wheels steering (for circulation), 4 wheels steering (for work)
Tyres size	Forestry tyres 420/85-28
Chassis	Integral chassis made of high strength steel. Floating motor-box set. Full shielding.
Engine location and layout	On the back, longitudinal
Driver's cab location	Central position between front axle and rear axle

	<b>ENGINE</b>
Denomination	Manufacturer : VOLVO PENTA
General description	Type : TAD583_VE – Stage 5
Number and disposition of cylinders	Inner combustion engine with reciprocating pistons and crankshaft
Maximum torque	Power rating : 175 Hp – Engine capacity : 5,13 l
Maximum rotation speed	Cycle : Diesel
Engine power supply mode	4 cylinders in line
Air filter type	950 nm at 1300 rotation/min
Ignition	2310
Engine cooling	Common rail fuel injection
	Dry, with cartridges
	By compression
	By forced water circulation and water cooler

	<b>CONFORT + CAB</b>
VISION + windscreen	Inclined, monobloc, anti-dust, anti-reflection, anti-rain.
Display and control	Full digital display (mulcher rotation, gauges, indicators, diagnostic, settings...)
Safety	Advancement control by front/rear foot pedal and manual reversing
Equipments	Lexan-Margard® safety glass 12 mm
	ROPS-FOPS-OPS approval
	New cab, air-conditioned, soundproof, pressurized and high comfort damping system
	Work light : 2 front headlights and 2 rear headlights
	High comfort seat (Public works type)
	Stereo USB-Bluetooth radio

	<b>EXTRA INFORMATION</b>
Fuel type	Diesel
Fuel tank	215 liters metallic tank fixed on the left side of the chassis
Hydraulic tank	195 liters metallic tank fixed on the right side of the chassis
Réservoir AdBlue	45 liters on the right in the hydraulic tank

## Mulcher technical description

### ***BF 401H 1800***

### ***MULCHER***

Rotor width	1,8 m
Rotor diameter	497 mm
Use	Forestry mulching/crushing
Tools	Fixed – 2 carbide tips Side scraper tools
Tools position on the rotor	Helical and V positions
Mechanical drive	1 Gates® Polychain belt
Curtain of chains	Simple curtain of chains
Protection door	Hydraulic with two (public works) heavy duty cylinders
Hydraulic rake	Hydraulic with two HARDOX® cylinders
Rolling	Heavy duty roller bearings with double rows of rollers. Made with mass cut steel bearing.
Ski	HARDOX 450® soles
Protections	Anti-wire, bolted and interchangeable cut in mass, chains and metal sheet antiprojections
Bearings	Mass cut steel bearing
Box/drive	Linde hydraulic engine
Counter blade	HARDOX® counter knives, inside chassis
Hitch	Specific hydraulic third point
Chassis	<b>HLE and HARDOX® steels</b>

## Tools

*Double carb tip*



**OF6**

## Dimension (mm)





